

FC-02 | Frangible Coupling 2" - Airsafe



COMPLIANCE:

- ICAO: Annex. 14 - Vol.
- FAA AC 150/5345-46
- EASA CS-ADR-DNS
- STANAG 3316
- SAC: GB/T 7256

BOARDING PASS

NAME OF PASSANGER

FROM:

TO:

DATE FLIGHT
 GAES2020

GATE SEAT
23 21B

BOARDING TIME

GATE CLOSSES 30 MINUTES BEFORE DEPARTURE

GOMINTEC

Uses

Applicable for installing elevated light on the flange.

Features

- Forging of premium aluminum alloy material with thermal stability technology for even mechanical property.
- Equal-strength structural design with even loading and less possibility of deforming.
- High-precision machining, fully guarantees the quality and precision of bases.
- Made of anti-corrosion aluminum with prior preservative treatment, durable in use.

Order Code

FC-02 - X - X

Type ↑ ↑ ↑

FC-02 = 2" pipe thread frangible couplings

Connection Method ↑ ↑

I = Insert in elevated light body base
O = Connect to the 2" extension pole

Thread Type ↑ ↑

G = 55° cylindrical pipe thread
NPT = 60° American national taper pipe thread
NPS = 60° American national straight pipe thread

Installation

Figure 1
On FL-10 Flange

Figure 2
On FL-12 Flange

Structure & Dimensions

FC-02-I

FC-02-O

FC-02-I : 20 x frangible couplings	
Packaging size	340 × 340 × 190 mm ³
Weight	Unit: 0,46kg / Gross: 11.3kg
FC-02-O : 16 x frangible couplings	
Packaging size	340 × 340 × 190 mm ³
Weight	Unit: 0,64kg / Gross: 12.3kg